



Product Code:	130037
Product Name:	GORI 37
Where to use:	Exterior wooden decks
Can sizes:	2.50 L - 5.00 L - 20.00 L

1 Product Description

1.1	Product Type:	Special extra durable, water based oil for wood decks outdoor.
1.2	Manufacturer:	Dyrup A/S - Gladsaxevej 300 - 2860 Søborg - Dänemark - Tel.: +45 39 57 93 00 - www.dyrup.com
1.3	Where to use	Outdoor wooden decks. For all kinds of wood including pressure impregnated or exotic wood species. If you want to treat a wooden deck made of larch, we recommend that you apply pre-treatment with GORI 11 or GORI 22.
1.4	Special qualities:	Enhances the structure of the wood. Protects against the elements. Protects surface against fungi and mould. gives the wood a beautiful glow. Quick drying - walkable after 1 hour. Gives the surface an anti-slip effect.
1.5	Colour:	• 9900 Incolore • 7804 Teak • 7805 Oak • 7808 Walnuss
1.6	Form supplied:	Ready to use.

2 Composition

2.1	Binder:	Special oil.
2.2	Solvents:	Water.
2.3	VOC content:	Out of scope.
2.4	Pigments:	Organic and inorganic pigments.

3 Technical Data

3.1	Specific gravity:	App. 1,02 g/ml.
-----	-------------------	-----------------

3.2	Viscosity:	12 sec. (4 mm/DIN cup).
3.3	Flash point:	n/a
3.4	Gloss:	Matt.
3.5	Solid content:	App. 17 w/w% / 16,1 v/v%.
3.6	Odoour:	Weak.
3.7	Coverage:	App.15 m ² /l, depending on the type of wood and the state of substrate.
3.8	Drying time:	<u>Recoatable</u> : App. 1 hour. <u>Through dry</u> : App. 25 hours - you can walk on the terrace 1 hour after application. Measured at 23 °C and standard humidity of 60%. Deviations may occur at different temperatures, humidity and layer thickness.
3.9	Weather resistance:	Water repellent.
3.10	Thinning:	Do not thin.
3.11	Storage.	Store frost free. Keep container firmly closed, dry and out of direct sunlight.
3.12	Shelf life:	3 years in unopened container. Limited shelf life after opening.

4 Surface and preparation

4.1	In general:	Stir well before and during application.
4.2	Substrate:	The surface must be clean, dry and solid.
4.3	Humidity / Moisture content:	Moisture content: Softwood: max 15% - Hardwood: max. 12%. Do not use at temperatures below 5 °C and/or above 80% relative humidity, based on a daily average.

5 Treatment

5.1	Application method:	Apply by brush or spray. Avoid application in direct sunlight.
5.2	Pre-treatment:	The surface must be clean, dry and solid. Clean surface with GORI Deck Cleaner to disinfect visible and non-visible mould and incrustations. Remove visible incrustations by scrubbing the surface with a brush. Rinse with clean water. If the wood is very dirty, you can use a high-pressure cleaner with moderate pressure. New and untreated wood should be treated against rot and fungi with GORI 11 or GORI 22. Hardwood and pressure-impregnated wood does not need to receive pre-treatment with a wood preservative.

- 5.3 Treatment: Apply 2 coats of GORI 37 along the wood grain wet on wet. After the second coat you can mix a coloured product 1:1 with GORI 37 Clear, so the wood does not become significantly darker. Do not use Clear alone without a pigmented base coat. The oil is applied until the wood is saturated. After each application, excess oil must be wiped off with a lint free cloth in order not to form a surface film. Surface film may cause the surface to peel and crack.
- 5.4 Cleaning of tools: Clean tools with soap and water.

6 Safety Precautions

- 6.1 In general: Common safety rules for work with paints and varnishes must be observed. Further information is available from Material Safety Data Sheet.
- 6.2 Safety instructions: Harmful to aquatic life with long lasting effects. Keep out of reach of children. If medical advice is needed, have product container or label at hand. Avoid release to the environment. Dispose of contents and container in accordance with all local, regional, national and international regulations. Contains 1,2-benzisothiazol-3(2H)-one, neodecanoic acid, cobalt salt, bis(1,2,2,6,6-pentamethyl-4-piperidyl) sebacate and 3-iodo-2-propynyl butylcarbamate. May produce an allergic reaction.

7 Disposal

- 7.1 Disposal: Do not empty into drains or into the environment. Product waste must not be poured into the sewers, water reserves or soil. Left over product should be handed in at your local waste disposal. Empty can may be recycled (check with your local waste disposal site or your local authorities).

The purpose of this Technical Data Sheet is to provide our clients with information about the properties and characteristics of the product. The information provided is based on tests conducted by us under usage conditions that comply with the prevailing standards. Our recommendations for use are for information only, and in no event shall they take precedence over any specific recommendation, taking into account the nature and conditions of a particular site, nor shall they engage PPG's liability. Before all applications of the product, clients should check that this document has not been amended by a more recent version, which takes into account new technical data. This version annuls and replaces all previous versions of Technical Data Sheets relating to this product.
